

# Investigation of the Geometry Effect on the Wall Shear Stress on the Aneurysm Wall

Nina Philipova<sup>1</sup>, Elena Nikolova<sup>1</sup>, Nikola Nikolov<sup>1</sup>, Vaniya Georgieva<sup>2</sup>,  
Stefan Radev<sup>1</sup>

<sup>1</sup> Institute of Mechanics, Bulgarian Academy of Sciences,  
Sofia, Bulgaria

philipova@imbm.bas.bg, elena@imbm.bas.bg, n.nikolov@imbm.bas.bg,  
stradev@imbm.bas.bg

<sup>2</sup> Hospital Sofamed, Sofia, Bulgaria  
top\_beauty@abv.bg

*Keywords: wall shear stress, Computational Fluid Dynamics, geometry parameters, regression equations*

The variation of wall shear stress (WSS) is hypothesized as a major cause for aneurysm rupture. Objective of many studies is to examine the critical values of WSS, that can lead to aneurysm hemorrhage. Following this aim the authors perform numerical simulations in ANSYS Workbench 14. Ideal aneurysm geometries are constructed in commercial package ANSYS Model Designer. Three main morphological factors are varied: diameter of parent vessel, aneurysm diameter and aneurysm height. Using numerical simulations (in commercial code ANSYS Fluent), contours of both total pressure and velocity magnitude in the symmetry plane, as well as contours of WSS on the parent vessel, and aneurysm walls are obtained. By applying commercial code STATISTIKA a special attention is paid on the WSS on aneurysmal wall and its 25th quartile. Regression equations are derived for the WSS on aneurysm wall depending on the above geometric parameters.